

Graduated measure, in high density polyethylene, with funnel type outlet and flexible extension.

Art.no. **3408/1** capacity 1 l

Art.no. **3408/2** capacity 2 l

Art.no. **3408/3** capacity 3 l

Art.no. **3408/5** capacity 5 l



Graduated, transparent measure, in oil and acid resistant polyethylene, stackable and unbreakable. Temperature range: -10° C +120°C.

Art.no. **3425** capacity 0.25 l - scale graduation 5 ml

Art.no. **3426** capacity 0.50 l - scale graduation 10 ml

Art.no. **3427** capacity 1 l - scale graduation 10 ml

Art.no. **3428** capacity 2 l - scale graduation 20 ml

Art.no. **3429** capacity 3 l - scale graduation 50 ml

Art.no. **3430** capacity 5 l - scale graduation 100 ml



Graduated measure, in high density polyethylene, with funnel type outlet, flexible extension with cap, protection cover. Suitable for the use with oil, fuel, antifreeze, windshield washer fluid, break fluid, battery fluid.

Art.no. **3447** capacity 1 l

Art.no. **3448** capacity 2 l

Art.no. **3449** capacity 5 l



Graduated measure, tin-plate, suitable for the use with oil, fuel and antifreeze.

With rigid, plastic discharge spout:

Art.no. **3408/05R** capacity 0.5 l

Art.no. **3408/1R** capacity 1 l

Art.no. **3408/2R** capacity 2 l



Art.no.
3408/05R

Art.no.
3408/1R

Art.no.
3408/2R

With flexible metal discharge spout:

Art.no. **3408/1FMS** capacity 1 l

Art.no. **3408/2FMS** capacity 2 l



Art.no.
3408/1FMS

Art.no.
3408/2FMS