



Art.no. **8318**

Pneumatic double diaphragm pump, selfpriming up to 5 m suction lift, working also in dry running condition, without any electric drive, suitable for the use also with fluids of higher viscosity and for fluids containing particles up to 3 mm size, body in PP, diaphragms in NBR + PTFE, balls in stainless steel, gaskets in EPDM, seats in PP. The pump is constructed in accordance with directive ATEX 2014/34/EU - zone 2.

Art.no. **7818**

Wall mounting bracket for pneumatic diaphragm pump.



Art.no. **7818**

 EX II 3/3 GD C IIB T 135°C

Art. no.	Max flow rate	Max suction lift	Comp. air supply	Connection compressed air inlet	Connections fluid inlet - outlet	Consumption compressed air	Weight	Dimensions (LxWxH) (mm)
8318	20 l/min	5 m	2 - 8 bar	1/4" BSP (F)	3/8" BSP (F)	110 l/min	1.1 kg	146x93x164



Art.no. **8319**

Pneumatic double diaphragm pump, selfpriming up to 5 m suction lift, working also in dry running condition, without any electric drive, suitable for the use also with fluids of higher viscosity and for fluids containing particles up to 3.5 mm size, body in aluminium, diaphragms in Hytrel® + PTFE, balls in PTFE, gaskets in Viton®, seats in aluminium. The pump is constructed in accordance with directive ATEX 2014/34/EU - zone 2.

Art.no. **7818**

Wall mounting bracket for pneumatic diaphragm pump.



Art.no. **7818**

 EX II 3/3 GD C IIB T 135°C

Art. no.	Max flow rate	Max suction lift	Comp. air supply	Connection compressed air inlet	Connections fluid inlet - outlet	Consumption compressed air	Weight	Dimensions (LxWxH) (mm)
8319	55 l/min	5 m	2 - 8 bar	1/4" BSP (F)	1/2" BSP (F)	200 l/min	4 kg	234x156x245

Art.no. **8320**

Art.no. **8321**

Pneumatic double diaphragm pump, working also in dry running condition, selfpriming up to 5 m suction lift, without any electric drive, suitable for the use also with fluids of higher viscosity and for fluids containing particles up to 4 mm (art.no. 8320) / 7,5 mm (art. no. 8321) size, body in aluminium, diaphragms in Hytrel® + PTFE, balls in PTFE, o - rings in Viton®, seats in aluminium.

The pump is constructed in accordance with directive ATEX 2014/34/EU - zone 2.

Art.no. **7818**

Wall mounting bracket for pneumatic diaphragm pump art.no. 8320.

Art.no. **7819**

Wall mounting bracket for pneumatic diaphragm pump art.no. 8321.



Art.no. **7818**
Art.no. **7819**

 EX II 3/3 GD C IIB T 135°C

Art. no.	Max flow rate	Max suction lift	Comp. air supply	Connection compressed air inlet	Connections fluid inlet - outlet	Consumption compressed air	Weight	Dimensions (LxWxH) (mm)
8320	100 l/min	5 m	2 - 8 bar	3/8" BSP (F)	3/4" BSP (F)	250 l/min	7 kg	265x175x245
8321	170 l/min			1/2" BSP (F)	1" BSP (F)	800 l/min	16 kg	370x222x364